

SAMTRON

95P 19-inch monitor



95P 19-inch monitor

The SAMTRON 95P is the ideal monitor for office and home users. Its large screen offers full clear visibility. The perfect flicker-free display eliminates eye strain. It has a horizontal frequency of 30-96kHz and 1,600 x 1,200 maximum resolution. In addition, the Plug & Play is perfectly realized through DDC and USB (optional).

The SAMTRON 95P meets the MPR-II and TCO'99(optional) emission standards for user safety.

The compact design of the SAMTRON 95P offers you the freedom to fully utilize your space without compromising clarity, safety or performance.

Ready for



USB Hub



Model: SAMTRON 95P



NUTEK



SAMTRON

416, Maetan-3Dong, Paldal-Gu, SuwonCity,
Kyungki-Do, Korea
442-373
Fax (82-331) 200-7803
<http://www.samtron.com>

Design and Specifications are subject to change without notice.

All brand and product names are Trademarks or Registered Trademarks of their respective companies.
Use of the Energy Star logo is not to be considered a product endorsement.

This device complies with FCC Class B, UL and CSA.

B0G 1999.12

Specifications Summary: Samtron 19" Color Monitor

CRT:	Size	19" diagonal
	Viewable image Size	18.0"
	Dot Pitch	0.22mm (Horizontal)
	Surface Treatment Deflection	Non-Glare, Multi-Layer Coated 90°
Resolution:	Resolution (recommended)	1280 x 1024@85Hz
	Maximum	1600 x 1200@75Hz
Pixel Frequency:	Maximum	205MHz
Scanning Frequency: (Auto Scanning)	Horizontal	30-96kHz
	Vertical	50-160Hz
Display Area:	Normal	352 x 264mm
	Maximum	366 x 275m
Microprocessor	Factory Saving Mode	10 modes
	User Saving Mode	12 modes
User Control:	Digital	Position, Size, Pincushion, Trapezoid, Pin-Balance, H-Moire, V-Moire, Parallelogram, Recall, Manual Degauss, Contrast, Brightness
Power:	Voltage	AC90-264V 60/50±3Hz, Universal Power
Plug & Play	DDC	1/2B/2Bi
	USB	Hub(up:1port,down:4Ports)(User Option)
Signal Input:	Connector	15 pin Female
Display Color:	Color Temperature	Can be selected from 5000°K to 9300°K with 100°K
Compatibility:	IBM	VGA2, 720 x 400 @70Hz
		VGA3, 640 x 480 @60Hz
	VESA	640 x 480 @85Hz
		800 x 600 @85Hz
		1024 x 768 @85,100Hz
	MAC	1280 x 1024 @75,85Hz
		1600 x 1200 @75Hz
		1152 x 870 @75Hz
Safety & EMI:	Safety	UL, CSA, TUV, IE950, Scandinavian, KOREA
	EMI Low-Radiation	FCC, DOC, CE, VCCI, KOREA TCO'99(option)
Dimensions:	W x H x D	469 x 471 x 493.5mm
Weight:	Axtnal	22.5kg
	Shipping	26.7kg
Power Management:	Regulation	EPA/NUTEK
		VESA DPMS

